



OPTIONAL EXTRAS

Motorized Pulley 165E

Specification	Availability
Total stainless steel option AISI 304 range TS7N with regreasable labyrinth seals	x
Food grade oil & grease - FDA & USDA recognized	x
Dust explosion proof Motorized Pulleys - ATEX 95 - Zone 22 - for applications handling dusty grain etc. According to European Directive 94/9/EC.	o
Total acid resistant stainless steel option - AISI 316	x
Black rubber lagging - Standard specifications (See page 82-83.) 1/8" smooth lagging - Hardness 60 ±5 Shore A	o
White smooth rubber lagging (FDA). Oil, fat & grease resistant	o
Special lagging (e.g. hot vulcanized)	o
Electromagnetic brake Min. RL increases by 1.97"	x
Mechanical backstop Min. RL does not increase with backstop option	x
Modified for vertical mounting	o
Modified for mounting between 5° and 90° (e.g. for magnetic separators)	o
Insulation class F with standard oil: (Allowable ambient temperature: -13°F/+104°F)	x
Insulation class H with synthetic oil: (Allowable ambient temperature: -13°F/+120°F)	Std.
Special motors for applications with no belt contact	o
Low noise drives for noise sensitive areas	x
Parallel shell	x
Thermal protector	Std.
IP66/67 Compact unpainted aluminum terminal box	Std.
IP66/67 Compact stainless steel terminal box- AISI 304 or 316 range	x
Straight or elbow connector with standard power cord	x
Straight connector with screened power cord (See page 86 for VFD precautions)	x
Straight connector with standard power cord (Stainless steel in AISI 304 range)	x
Voltage: single voltage (460) stator (Y winding) wired for 460v/3ph/60 Hz at terminal box	Std.
single voltage (230) stator (Y winding) wired for 230v/3ph/60 Hz at terminal box	x
Special voltage motors	x
CSA approved motors	x

x = Optional extra's

o = An option with certain limitations. Please refer to Technical precautions pages 78-98!

Std. = Fitted as standard