



ORDERING* INFORMATION

Motorized Pulleys

Contact Person _____ Date _____ Ref # _____
 Company _____
 Address _____
 Phone _____ Fax _____ Email _____

Diameter (in)	Roller Length (in)	Belt Speed (fpm)	Lagging Material	Type of Oil
<input type="checkbox"/> 5.45	<input type="checkbox"/> 11.81	<input type="checkbox"/> 10	<input type="checkbox"/> black rubber, diamond pattern	<input type="checkbox"/> standard
<input type="checkbox"/> 6.49	<input type="checkbox"/> 12.60	<input type="checkbox"/> 12	<input type="checkbox"/> black rubber, smooth pattern	<input type="checkbox"/> synthetic
<input type="checkbox"/> 8.50	<input type="checkbox"/> 13.78	<input type="checkbox"/> 14	<input type="checkbox"/> white rubber, smooth pattern	<input type="checkbox"/> food grade
<input type="checkbox"/> 12.64	<input type="checkbox"/> 15.75	<input type="checkbox"/> 18	<input type="checkbox"/> red ceramic bonded to pulley shell	Motor Insulation
<input type="checkbox"/> 15.91	<input type="checkbox"/> 17.72	<input type="checkbox"/> 24	<input type="checkbox"/> green ceramic vulcanized into rubber	
<input type="checkbox"/> 19.72	<input type="checkbox"/> 19.69	<input type="checkbox"/> 30	Lagging Bond	<input type="checkbox"/> class F (standard)
<input type="checkbox"/> 24.80	<input type="checkbox"/> 21.65	<input type="checkbox"/> 38		<input type="checkbox"/> cold bonded
<input type="checkbox"/> 31.50	<input type="checkbox"/> 23.62	<input type="checkbox"/> 48	<input type="checkbox"/> hot vulcanized	Type of Crown
Power (HP)	<input type="checkbox"/> 25.59	<input type="checkbox"/> 60	Lagging Thickness	
	<input type="checkbox"/> 27.56	<input type="checkbox"/> 76		<input type="checkbox"/> 1/8 inch
<input type="checkbox"/> 29.53	<input type="checkbox"/> 96	Termination (select one)	<input type="checkbox"/> 1/4 inch	<input type="checkbox"/> no crown
<input type="checkbox"/> 31.50	<input type="checkbox"/> 120		<input type="checkbox"/> 300	Mounting Brackets
<input type="checkbox"/> 0.13	<input type="checkbox"/> 33.46	<input type="checkbox"/> 384	<input type="checkbox"/> standard paint	
<input type="checkbox"/> 0.15	<input type="checkbox"/> 35.43	<input type="checkbox"/> 480	<input type="checkbox"/> nickel plated	
<input type="checkbox"/> 0.25	<input type="checkbox"/> 37.40	<input type="checkbox"/> 600	<input type="checkbox"/> none	
<input type="checkbox"/> 0.33	<input type="checkbox"/> 39.37	<input type="checkbox"/> 768	Type of Holdback	
<input type="checkbox"/> 0.50	<input type="checkbox"/> 41.34	<input type="checkbox"/> 960		<input type="checkbox"/> mech. backstop, clockwise
<input type="checkbox"/> 0.75	<input type="checkbox"/> 43.31	<input type="checkbox"/> 1064	<input type="checkbox"/> mech. backstop, counterclockwise	
<input type="checkbox"/> 1.0	<input type="checkbox"/> 45.28	Voltage	<input type="checkbox"/> internal brake	
<input type="checkbox"/> 1.5	<input type="checkbox"/> 47.24		<input type="checkbox"/> 208v	<input type="checkbox"/> external brake shaft
<input type="checkbox"/> 2.0	<input type="checkbox"/> 49.21	<input type="checkbox"/> 230v	Type of Seals	
<input type="checkbox"/> 3.0	<input type="checkbox"/> 51.18	<input type="checkbox"/> 380v		<input type="checkbox"/> standard
<input type="checkbox"/> 4.0	<input type="checkbox"/> 53.15	<input type="checkbox"/> 460v	<input type="checkbox"/> regreasable	
<input type="checkbox"/> 5.5	<input type="checkbox"/> 55.12	<input type="checkbox"/> 575v	Material & Surface Finish	
<input type="checkbox"/> 7.5	<input type="checkbox"/> 57.09	Phase & Frequency		<input type="checkbox"/> mild steel, standard paint
<input type="checkbox"/> 10	<input type="checkbox"/> 59.06		<input type="checkbox"/> 3ph/60Hz	<input type="checkbox"/> total stainless steel
<input type="checkbox"/> 15	<input type="checkbox"/> 61.02	<input type="checkbox"/> 3ph/50Hz	<input type="checkbox"/> semi-rust free	
<input type="checkbox"/> 20	<input type="checkbox"/> 62.99	<input type="checkbox"/> 1ph/60Hz	Other Special Options	
<input type="checkbox"/> 25	<input type="checkbox"/> 64.96	<input type="checkbox"/> 1ph/50Hz		<input type="checkbox"/> vertical mount
<input type="checkbox"/> 30	<input type="checkbox"/> 66.93		<input type="checkbox"/> non-horizontal mount	
<input type="checkbox"/> 40	<input type="checkbox"/> 68.90		<input type="checkbox"/> CSA approved motor	
<input type="checkbox"/> 50	<input type="checkbox"/> 70.87		<input type="checkbox"/> dust explosion proof (per ATEX 95, Zone 22)	
<input type="checkbox"/> 61	<input type="checkbox"/> 72.83			
<input type="checkbox"/> 75	<input type="checkbox"/> 74.80			
<input type="checkbox"/> 100	<input type="checkbox"/> 76.77			
<input type="checkbox"/> 122	<input type="checkbox"/> 78.74			
<input type="checkbox"/> 150	<input type="checkbox"/> Other			
<input type="checkbox"/> 180				
Quantity _____ Motorized Pulley(s) Quantity _____ Idler Pulley(s) Special Comments: _____ _____ _____				

* Note that this form displays all powers, speeds, and options available from Rulmecca. Some combinations are unavailable (e.g. 100 HP is not available in 12.64" diameter.) For interactive ordering sheet go to www.rulmecacorp.com.