



## OPTIONAL EXTRAS

### Motorized Pulley 320L, 320M & 320H

Specification	Availability
Total stainless steel option AISI 304 range TS9N with regreasable labyrinth seals	x
Total stainless steel option AISI 304 range TS10N with standard seals	x
Semi-rust free option TS11N with regreasable labyrinth seals	x
Semi-rust free option TS12N with standard seals	x
Regreasable labyrinth seals	x
Food grade oil & grease - FDA & USDA recognized	x
Dust explosion proof Motorized Pulleys - ATEX 95 - Zone 22 - for applications handling of dusty grain etc. According to European Directive 94/9/EC.	x
Total acid resistant stainless steel option - AISI 316	x
Black rubber lagging - Standard specifications (See page 80.)	
5/16" diamond lagging - Hardness 60 ±5 Shore A ≤ 7.5 HP	x
1/4" diamond lagging - Hardness 60 ±5 Shore A 10 HP	o
White smooth rubber lagging (FDA listed) Oil, fat & grease resistant	o
Special lagging (e.g. hot vulcanized)	o
Electromagnetic brake Min RL increases by 3.94"	x
Mechanical backstop Min RL does not increase for 320L,	x
Min. RL increases by 1.97" for 320 M & 320H	x
Modified for vertical mounting	o
Modified for mounting between 5° and 90° (e.g. for magnetic separators)	o
Insulation class F with standard oil: (Allowable ambient temperature -13°F/+104°F)	Std.
Insulation class H with synthetic oil: (Allowable ambient temperature -13°F/+120°F)	x
Special motors for applications with no belt contact	o
Low noise drives for noise sensitive areas	x
Parallel shell (i.e. no crown)	x
Thermal protector	Std.
IP66/67 Yellow powder coated aluminum terminal box	Std.
IP66/67 Gray powder coated aluminum terminal box (food grade approved)	x
IP66/67 Compact powder coated aluminum terminal box (food grade approved) ≤ 5.5 HP only	o
IP66/67 Compact stainless steel terminal box - AISI 304 or 316 range ≤ 5.5 HP only	o
Straight or elbow connector with standard power cord ≤ 5.5 HP only	x
Straight connector with screened power cord (See page 86 for VFD precautions) ≤ 5.5 HP only	x
Straight connector with power cord (Stainless steel in AISI 304 range) ≤ 5.5 HP only	x
Voltage: ≤ 5.5 HP dual voltage (230/460) stator (YY/Y winding) wired for 460v/3ph/60 Hz at terminal box	Std.
≤ 5.5 HP dual voltage (230/460) stator (YY/Y winding) wired for 230v/3ph/60 Hz at terminal box	x
≥ 7.5 HP single voltage (460) stator (Y winding) wired for 460v/3ph/60 Hz at terminal box	Std.
≥ 7.5 HP single voltage (230) stator (YY winding) wired for 230v/3ph/60 Hz at terminal box	x
2 speed motors	x
Special voltage motors	x
Single phase motors	o
CSA approved motors	x

x = Optional extras

o = An option with certain limitations. Please refer to Technical precautions pages 76-86!

Std. = Fitted as standard