



OPTIONAL EXTRAS

Motorized Pulley 800M & 800H

| Specification | Availability | |
|---|---------------------------------------|------|
| Semi-rust-free option | TS11 with regreasable labyrinth seals | x |
| Semi-rust-free option | TS12 with standard seals | x |
| Regreasable labyrinth seals | | x |
| Dust explosion proof Motorized Pulleys - ATEX 95 - Zone 22 - for applications handling of dusty grain etc. According to European Directive 94/9/EC. | | x |
| Standard black rubber lagging (See page 80.) | | |
| 3/8" full smooth lagging - Hardness 60 ±5 Shore A | | o |
| 3/8" full diamond lagging - Hardness 60 ±5 Shore A | | o |
| 3/8" partial smooth lagging - Hardness 60 ±5 Shore A | | o |
| White smooth rubber lagging (FDA listed) - Oil, fat & grease resistant | | o |
| Special lagging - e.g. hot vulcanized, partial, and ceramic (See page 80.) | | o |
| External brake shaft (for mechanical brake by others) | | x |
| Mechanical backstop | Min. RL = 37.40" for 800M | x |
| | Min. RL = 45.28" for 800H ≤ 100 HP | x |
| | Min. RL = 55.12" for 800H > 100 HP | x |
| Insulation class F with standard oil: (allowable ambient temperature: -13°F/+104°F) | | Std. |
| Insulation class H with synthetic oil: (allowable ambient temperature: -13°F/+120°F) | | x |
| Parallel shell | | x |
| Thermal protector | | Std. |
| Voltage: Single voltage (460) stator (Y winding) wired for 460v/3ph/60 Hz at terminal box | | Std. |
| IP66/67 Standard yellow powder coated cast iron terminal box | | Std. |
| Special voltage motors | | x |
| CSA approved motors | | x |

x = Optional extras

o = An option with certain limitations. Please refer to Technical precautions pages 76-86

Std. = Fitted as standard